



5.5 KWH

AM-2

REVISION 2

V 2.0

- Low self discharge
- High cycle and service life
- Easy wall mount or shelf rack installation
- Excellent high temperature performance
- Advanced BMS with current limiting function
- Compatible with most inverters and chargers
- High energy density and conversion efficiency
- Cloudlink integration ready for wifi monitoring
- Complete with integrated Battery Management System
- Heavy duty side handles for easy handling and mounting on the wall
- Built in protection for over-charge, over-discharge & over-temperature
- CAN Bus, fully integrates and communicates with leading Inverter brands

www.hubblelithium.co.za



TECHNICAL DATA

ITEM	SPECIFICATIONS
Model	Hubble AM-2
*Rated Capacity (5HR)	116 Ah
Nominal Voltage	48 V
Design Capacity	5.5 KWH
Equalized Charge Voltage	53.8 V
Max. Continuous Charging Current	105 A
Max. Continuous Discharging Current	105 A
C Rating	1.0 C
Weight	Approx. 42 Kg
Display	None
Parallel	Parallel connection up to 15 packs with full communications
Dimensions (WxDxH) mm	375mm x 145mm x 467mm
Ports	1x CAN-bus, 2x Battery Link Ports
Cells	New Li-ion Prismatic Cells
Design Life	+/- 15 Years
Cycle Life @ 1C	+/- 6000 Cycles @ 50% DOD, Above 3000 cycles @ 100% DOD
Certification	CE, UN38.3, GBT31484-2015, GBT31485-2015, GBT31486-2015
Outer Package Material	White bake lacquer steel case
Operating Temperature	Charging: 0 to +55°C Discharging: -20 to +55°C Storage: -20 to +55°C
Protection	Electronic Circuit Breaker, BMS Voltage Protection, Current Limiting

**Due to continuous product improvements specifications are subject to change without prior notice.
Ah design capacity nominally is between 110Ah and 120Ah



www.hubblelithium.co.za